

**Section 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name:** NANOLEX GLASS CLEANER

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Use of substance / mixture:** PC35: Washing and cleaning products (including solvent based products).

**1.3. Details of the supplier of the safety data sheet**

**Company name:** Infnitec GmbH  
Matzenberg 171  
Saarbrücken  
D-66115  
Germany

**Tel:** +4968198 800306

**Email:** [a.neuner@infnitec-gmbh.de](mailto:a.neuner@infnitec-gmbh.de)

**1.4. Emergency telephone number**

**Emergency tel:** Medical Emergency information in case of poisoning: Poison Information Center Mainz -  
24h - Phone: +49 (0) 6131 19240 (advisory service in German or English language)

**Section 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification under CLP:** Eye Irrit. 2: H319

**Most important adverse effects:** Causes serious eye irritation.

**2.2. Label elements**

**Label elements:**

**Hazard statements:** H319: Causes serious eye irritation.

**Hazard pictograms:** GHS07: Exclamation mark



**Signal words:** Warning

**Precautionary statements:** P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P101: If medical advice is needed, have product container or label at hand.

P501: Dispose of contents and container to an approved waste disposal plant.

P102: Keep out of reach of children.

**2.3. Other hazards**
**PBT:** This product is not identified as a PBT/vPvB substance.

**Section 3: Composition/information on ingredients**
**3.2. Mixtures**
**Hazardous ingredients:**
**PROPAN-2-OL**

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	1-10%

**2-BUTOXYETHANOL**

203-905-0	111-76-2	-	Acute Tox. 4: H332; Acute Tox. 4: H312; Acute Tox. 4: H302; Eye Irrit. 2: H319; Skin Irrit. 2: H315	1-10%
-----------	----------	---	---	-------

**KOKOSALKYL(FRAKTIONIERT)DIMETHYLAMINOXID**

263-016-9	61788-90-7	-	Skin Irrit. 2: H315; Eye Dam. 1: H318; Aquatic Chronic 2: H411; Aquatic Acute 1: H400	<1%
-----------	------------	---	---	-----

**Section 4: First aid measures**
**4.1. Description of first aid measures**
**Skin contact:** Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water.

**Inhalation:** Not applicable.

**4.2. Most important symptoms and effects, both acute and delayed**
**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**4.3. Indication of any immediate medical attention and special treatment needed**
**Immediate / special treatment:** Not applicable.

## Section 5: Fire-fighting measures

### 5.1. Extinguishing media

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

**Advice for fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

## Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Mark out the contaminated area with signs and prevent access to unauthorised personnel. Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

### 6.2. Environmental precautions

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

### 6.4. Reference to other sections

**Reference to other sections:** Refer to section 8 of SDS.

## Section 7: Handling and storage

### 7.1. Precautions for safe handling

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage conditions:** Store in a cool, well ventilated area. Keep container tightly closed.

### 7.3. Specific end use(s)

**Specific end use(s):** No data available.

## Section 8: Exposure controls/personal protection

### 8.1. Control parameters

**SAFETY DATA SHEET**  
 NANOLEX GLASS CLEANER

**Hazardous ingredients:**
**PROPAN-2-OL**
**Workplace exposure limits:**
**Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	999 mg/m <sup>3</sup>	1250 mg/m <sup>3</sup>	-	-

**2-BUTOXYETHANOL**

UK	25 ppm	50 ppm	-	-
----	--------	--------	---	---

**DNEL/PNEC Values**
**Hazardous ingredients:**
**PROPAN-2-OL**

Type	Exposure	Value	Population	Effect
DNEL	Dermal	888mg/kg	Workers	Systemic
DNEL	Inhalation	500mg/kg	Workers	Systemic
PNEC	Fresh water	140,9mg/l	-	-
PNEC	Marine water	140,9mg/l	-	-
PNEC	Microorganisms in sewage treatment	2.251mg/l	-	-
PNEC	Fresh water sediments	552mg/kg	-	-
PNEC	Marine sediments	552mg/kg	-	-
PNEC	Water	160mg/kg	-	-
PNEC	Soil (agricultural)	28mg/kg	-	-

**2-BUTOXYETHANOL**

Type	Exposure	Value	Population	Effect
DNEL	Inhalation	246 mg/m	Workers	Local
DNEL	Inhalation	89 mg/kg	Workers	Systemic
DNEL	Inhalation	1,091 mg/m	Workers	Systemic
DNEL	Inhalation	125 mg/kg	Workers	Systemic
DNEL	Inhalation	98 mg/m	Workers	Systemic
PNEC	Fresh water	8,8 mg/l	-	-
PNEC	Marine water	0,88 mg/l	-	-
PNEC	Microorganisms in sewage treatment	463 mg/l	-	-
PNEC	Soil (agricultural)	2,33 mg/kg	-	-

**KOKOSALKYL(FRAKTIONIERT)DIMETHYLAMINOXID**

Type	Exposure	Value	Population	Effect
------	----------	-------	------------	--------

**SAFETY DATA SHEET**  
 NANOLEX GLASS CLEANER

Page: 5

DNEL	Inhalation	15,5	Workers	Systemic
DNEL	Dermal	11 mg/kg	Workers	Systemic
DNEL	Inhalation	3,8	Consumers	Systemic
DNEL	Dermal	5,5 mg/kg	Consumers	Systemic
DNEL	Oral	0,44	Consumers	Systemic
PNEC	Fresh water	0,0335 mg/ml	-	-
PNEC	Marine water	0,00335 mg/ml	-	-
PNEC	Microorganisms in sewage treatment	24 mg/ml	-	-
PNEC	Fresh water sediments	1,14 mg/kg	-	-
PNEC	Marine sediments	0,114 mg/kg	-	-
PNEC	Soil (agricultural)	0,906 mg/kg	-	-
PNEC	Food chain	11,1 mg/kg	-	-

**8.2. Exposure controls**

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Protective gloves.

**Eye protection:** Tightly fitting safety goggles. Ensure eye bath is to hand.

**Skin protection:** Protective clothing.

**Section 9: Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

**State:** Liquid

**Colour:** Colourless

**Odour:** Characteristic odour

**pH:** 8,1

**9.2. Other information**

**Other information:** No data available.

**Section 10: Stability and reactivity**
**10.1. Reactivity**

**Reactivity:** Stable under recommended transport or storage conditions.

**10.2. Chemical stability**

**Chemical stability:** Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

**Hazardous reactions:** Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

**SAFETY DATA SHEET**  
 NANOLEX GLASS CLEANER

**10.4. Conditions to avoid**

**Conditions to avoid:** Heat.

**10.5. Incompatible materials**

**Materials to avoid:** Strong oxidising agents. Strong acids.

**10.6. Hazardous decomposition products**

**Haz. decomp. products:** In combustion emits toxic fumes.

**Section 11: Toxicological information**
**11.1. Information on toxicological effects**
**Hazardous ingredients:**
**PROPAN-2-OL**

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

**2-BUTOXYETHANOL**

IVN	RAT	LD50	307	mg/kg
ORL	MUS	LD50	1230	mg/kg
ORL	RAT	LD50	470	mg/kg

**KOKOSALKYL(FRAKTIONIERT)DIMETHYLAMINOXID**

DERMAL	RBT	LD50	300-2000	mg/kg
ORAL	RAT	LD50	2000	mg/kg

**Relevant hazards for product:**

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated

**Excluded hazards for substance:**

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	-	No hazard: calculated
Acute toxicity (ac. tox. 3)	-	No hazard: calculated
Acute toxicity (ac. tox. 2)	-	No hazard: calculated
Acute toxicity (ac. tox. 1)	-	No hazard: calculated
Skin corrosion/irritation	-	No hazard: calculated

**SAFETY DATA SHEET**  
 NANOLEX GLASS CLEANER

Page: 7

Respiratory/skin sensitisation	-	No hazard: calculated
Germ cell mutagenicity	-	No hazard: calculated
Carcinogenicity	-	No hazard: calculated
Reproductive toxicity	-	No hazard: calculated
STOT-single exposure	-	No hazard: calculated
STOT-repeated exposure	-	No hazard: calculated
Aspiration hazard	-	No hazard: calculated

**Symptoms / routes of exposure**

**Skin contact:** There may be irritation and redness at the site of contact.

**Eye contact:** There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

**Ingestion:** There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest.

**Delayed / immediate effects:** Immediate effects can be expected after short-term exposure.

**Section 12: Ecological information**
**12.1. Toxicity**

**Hazardous ingredients:**

**PROPAN-2-OL**

FISH	96H LC50	10.000	mg/l
------	----------	--------	------

**KOKOSALKYL(FRAKTIONIERT)DIMETHYLAMINOXID**

Daphnia magna	48H EC50	1-10	mg/l
FISH	96H LC50	1-10	mg/l
GREEN ALGA (Selenastrum capricornutum)	48H EC50	0,1-1	mg/l

**12.2. Persistence and degradability**

**Persistence and degradability:** Biodegradable.

**12.3. Bioaccumulative potential**

**Bioaccumulative potential:** No bioaccumulation potential.

**12.4. Mobility in soil**

**Mobility:** Readily absorbed into soil.

**12.5. Results of PBT and vPvB assessment**

**PBT identification:** This product is not identified as a PBT/vPvB substance.

**12.6. Other adverse effects**

**Other adverse effects:** Negligible ecotoxicity.

**Section 13: Disposal considerations**

**13.1. Waste treatment methods**

**Disposal operations:** Transfer to a suitable container and arrange for collection by specialised disposal company.

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**Section 14: Transport information**

**Transport class:** This product does not require a classification for transport.

**Section 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Specific regulations:** Not applicable.

**15.2. Chemical Safety Assessment**

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

**Section 16: Other information**

**Other information**

**Other information:** This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

\* indicates text in the SDS which has changed since the last revision.

**Phrases used in s.2 and s.3:** H225: Highly flammable liquid and vapour.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H315: Causes skin irritation.

H318: Causes serious eye damage.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H411: Toxic to aquatic life with long lasting effects.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.



**INFINITEC**

GMBH

Nanolex Car Care  
Matzenberg 171  
66115 Saarbrücken  
Tel.: +49 681. 906 776 50

