

NANOLEX ULTRA GLASS



Page: 1 Compilation date: 03.02.2020

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: NANOLEX ULTRA GLASS

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC9a: Coatings and paints, thinners, paint removers.

1.3. Details of the supplier of the safety data sheet

Company name: Infinitec GmbH

Matzenberg 171 Saarbrücken D-66115 Germany

Tel: +4968198 800306

Email: a.neuner@infinitec-gmbh.de

1.4. Emergency telephone number

Emergency tel: Medical Emergency information in case of poisoning: Poison Information Center Mainz -

24h - Phone: +49 (0) 6131 19240 (advisory service in German or English language)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT SE 3: H336; Eye Irrit. 2: H319; Flam. Liq. 2: H225 Most important adverse effects: Highly flammable liquid and vapour. Causes serious eye irritation. May cause

drowsiness or dizziness.

2.2. Label elements

Label elements:

Hazard statements: H225: Highly flammable liquid and vapour. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness. Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark



Signal words: Danger

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.



NANOLEX ULTRA GLASS



Page: 2

P241: Use explosion-proof electrical/ventilating/lighting/... equipment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.
Rinse skin with water .
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

PROPAN-2-OL

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319;	>90%
			STOT SE 3: H336	

HYDROGEN CHLORIDE

231-595-7	7647-01-0	-	Acute Tox. 3: H331; Skin Corr. 1A:	<1%	
			H314; Press. Gas: H280		

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

Ingestion: Wash out mouth with water.

Inhalation: Not applicable.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.
 Eye contact: There may be pain and redness. The eyes may water profusely. There may be severe pain. The vision may become blurred. May cause permanent damage.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Nanolex Car Care Matzenberg 171 66115 Saarbrücken Tel.: +49 681. 906 776 50

SAFETY DATA SHEET

NANOLEX ULTRA GLASS



Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

 Personal precautions:
 Mark out the contaminated area with signs and prevent access to unauthorised

 personnel. Do not attempt to take action without suitable protective clothing - see section

 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

7.3. Specific end use(s)

Specific end use(s): No data available.



NANOLEX ULTRA GLASS



Page: 4

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PROPAN-2-OL

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	999 mg/m3	1250 mg/m3	-	-
		-		

HYDROGEN CHLORIDE

UK 8 mg/m3 8 mg/m3

DNEL/PNEC Values

NANOLEX ULTRA GLASS

Туре	Exposure	Value	Population	Effect
DNEL	Dermal	888 mg/kg	Workers	Systemic
DNEL	Inhalation	500 mg/m3	Workers	Systemic
PNEC	Fresh water	140,9 mg/l	-	-
PNEC	Marine water	140,9 mg/l	-	-
PNEC	Microorganisms in sewage treatment	2,251 mg/l	-	-
PNEC	Fresh water sediments	552 mg/kg	-	-
PNEC	Marine sediments	552 mg/l	-	-
PNEC	Soil (agricultural)	28 mg/kg	-	-

Hazardous ingredients:

PROPAN-2-OL

Туре	Exposure	Value	Population	Effect
DNEL	Dermal	888mg/kg	Workers	Systemic
DNEL	Inhalation	500mg/kg	Workers	Systemic
PNEC	Fresh water	140,9mg/l	-	-
PNEC	Marine water	140,9mg/l	-	-
PNEC	Microorganisms in sewage treatment	2.251mg/l	-	-
PNEC	Fresh water sediments	552mg/kg	-	-
PNEC	Marine sediments	552mg/kg	-	-
PNEC	Water	160mg/kg	-	_

Nanolex Car Care Matzenberg 171 66115 Saarbrücken Tel.: +49 681. 906 776 50

cleaner faster longer www.nanolex.de

SAFETY DATA SHEET

NANOLEX ULTRA GLASS

						Page:	5
	PNEC		Soil (agricultural)	28mg/kg	-	-	
8.2	. Exposure co	ontrols					
	Engineering	q measures:	Ensure there is sufficie	nt ventilation of the are	a.		,
	-	-	Self-contained breathir			rgency.	
			Protective gloves.	• • • •			
	Eye	e protection:	Tightly fitting safety goo	ggles. Ensure eye bath	is to hand.		
	Skir	n protection:	Protective clothing.				
Section	on 9: Physic	cal and cher	nical properties				
9.1	. Information	on basic phy	sical and chemical pro	operties			
		State:	Liquid				
		Colour:	Colourless				
		Odour:	Characteristic odour				
	Fla	ash point°C:	15				
9.2	. Other inform	nation					
	Other	information:	No data available.				
Section	on 10: Stabi	lity and read	ctivity				
10.	1. Reactivity						
		Reactivity:	Stable under recomme	nded transport or stora	ge conditions.		
10.2	2. Chemical s	stability					
	Chemi	cal stability:	Stable under normal co	onditions.			
10.3	3. Possibility	of hazardous	s reactions				
	Hazardou	is reactions:	Hazardous reactions w	vill not occur under norr	nal transport or storage	conditions.	
			Decomposition may oc	cur on exposure to cor	ditions or materials list	ed below.	
10.4	4. Conditions	to avoid					
	Conditio	ons to avoid:	Heat.				
10.	5. Incompatib	ole materials					
	Materia	als to avoid:	Strong oxidising agents	s. Strong acids.			
	6. Hazardous	decompositi	on products				
10.			In combustion emits to:	xic fumes.			
10.0	Haz. decom	p. products:					
	Haz. decom on 11: Toxic		ormation				
Sectio		cological inf					

Nanolex Car Care Matzenberg 171 66115 Saarbrücken Tel.: +49 681. 906 776 50

SAFETY DATA SHEET

NANOLEX ULTRA GLASS



Page: 6

Hazardous ingredients:

PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MUS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	gm/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:	There may be irritation and redness at the site of contact.
Eye contact:	There may be pain and redness. The eyes may water profusely. There may be severe
	pain. The vision may become blurred. May cause permanent damage.
Ingestion:	There may be soreness and redness of the mouth and throat. Nausea and stomach
	pain may occur.
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest.
	Increase offer the same because stand of the short terms are as a

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

PROPAN-2-OL

		FISH	96H LC50	10.000	mg/l
--	--	------	----------	--------	------

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.



NANOLEX ULTRA GLASS



Page: 7

13.1. Waste treatment method	ls
Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal
	company.
NB:	The user's attention is drawn to the possible existence of regional or national
	regulations regarding disposal.
ection 14: Transport inform	ation
14.1. UN number	
UN number:	UN1219
14.2. UN proper shipping nan	ıe
Shipping name:	ISOPROPANOL (ISOPROPYL ALCOHOL)
	(PROPAN-2-OL; HYDROGEN CHLORIDE)
14.3. Transport hazard class(
Transport class:	
14.4. Packing group	
Packing group:	
14.5. Environmental hazards	
Environmentally hazardous:	No Marine pollutant: No
14.6. Special precautions for	
Special precautions:	No special precautions.
Tunnel code:	
Transport category:	2
ection 15: Regulatory inforr	nation
15.1. Safety, health and enviro	onmental regulations/legislation specific for the substance or mixture
Specific regulations:	
15.2. Chemical Safety Assess	
Chemical safety assessment:	A chemical safety assessment has not been carried out for the substance or the mixture
	by the supplier.
ection 16: Other information	n
ection 16: Other information Other information	n
Other information	n This safety data sheet is prepared in accordance with Commission Regulation (EU) No
Other information	



NANOLEX ULTRA GLASS



Page: 8

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.H314: Causes severe skin burns and eye damage.H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H336: May cause drowsiness or dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.